



Eco Version

High Output Version

# Audible Signals - Industrial ECO TLM AUDIBLE MODULES

## Industrial LED-TLM Eco Tower Light > Audible Modules

### Product overview

These audible modules have been designed for use in conjunction with the Moflash LED-TLM Eco Tower Light Module range. They are a simple fix addition that offers an audible warning signal in addition to the multiple visual ones that the tower offers.

The module can be pre-set with either a pulsed or continuous tone. The Eco buzzers have been designed for local indication only but a higher decibel output version (Ac only) is available.

This has two dB outputs selectable by a slide switch inside the enclosure.

### Features



- Continuously rated
- Low current consumption
- Cost effective audible solution
- Quick & easy installation or upgrade

### Material

Black ABS Plastic



### ECO TLM-AUD-02 >

<b>Code No:</b>	LED-TLM-AUD-02
<b>Voltage:</b>	24v Dc ---
<b>Operating Temperature:</b>	-25 to +55 °C
<b>Current:</b>	55mA
<b>Pulsed Tone Rate:</b>	60/80 (time/min)
<b>Output dB:</b>	100
<b>IP Protection:</b>	IP65






### ECO TLM-AUD-04 >

<b>Code No:</b>	LED-TLM-AUD-04
<b>Voltage:</b>	85-275v Ac ~
<b>Operating Temperature:</b>	-25 to +55 °C
<b>Current:</b>	<55mA
<b>Output dB:</b>	80
<b>IP Protection:</b>	IP54



### HIGH OUTPUT TLM-AUD120-04 >

<b>Code No:</b>	LED-TLM-AUD120-04
<b>Voltage:</b>	85-275v Ac ~
<b>Operating Temperature:</b>	-25 to +55 °C
<b>Current:</b>	<20
<b>Output dB:</b>	100-120 selectable
<b>IP Protection:</b>	IP65



APPROVALS and  
CONFORMITIES

