



Kenmerken

Gamma	060 Commando- /Veiligheidsvoorzieningen
Component	Tweehandenbediening
Type	Hellende twee hand bedieningsstation in aluminium
Code	060CL2MA
Omschrijving	Hellende twee hand bedieningsstation, grijs, aluminium
Kleur	Grijs RAL7016
Gewicht - gr	1461,000
Douanetarief	85371098
GTIN	8052878050887

Technische gegevens

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Compliance with standards	IEC-EN60204-1, UNI EN ISO 13849-1, UNI EN ISO 13851
Operating temperatures	-40° ÷ +70° C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK08 (IEC-EN62262)
Manufacturing process	Diecasting
Material	Aluminum Al Si 12
Screw material	ZAMAK zinc alloy
Screw type	M10 - slotted head type 6mm flat blade
Painting	Polyester powder coating
Rated insulation voltage	Ui 690V - Uimp 4KV (IEC-EN60947-1)
Protection against electric shock	Class I (IEC-EN61140)
Pushbutton characteristics	See the single items 020PTFAR-020PTFFGR-020GE11
Safety accessory	060MCP2M - 2 hand simultaneous action controller
Warranty period	18 months

Technische tekeningen

